

Quickie® 2HP

Ultra-Light

The Quickie 2HP is the lightest folding chair in the Quickie 2 Family. In addition to all the features of the Quickie 2, the Quickie 2HP also includes a fixed front frame for a more solid ride. The Quickie 2HP is ideal for those who demand high performance, low maintenance and everyday manual mobility.



Quickie 2HP Highlights:

- Fixed front frame provides a shorter, lighter, more rigid chair
- Performance wheel and caster options
- Increased maneuverability and propulsion



Quickie®

FOLDING FAMILY

Quickie Folding Chairs – A complete folding line to suit your mobility needs.

Ultra-Light



Lightweight



Positioning

Heavy Duty



Pediatrics



| Quickie 2 & Quickie 2 Kids & Quickie 2 HD | | | | | | | |
|--|---------------------------|-----------------------|--------------------|--------------------|----------------------|--|--|
| Front Seat Height (For Standard Frames Only) | | | | | | | |
| CASTER FORK MOUNTING HOLE | 5" LP POLY 5 1/4" FORK | 5" LP POLY 7" FORK | 6" PNEU 6" FORK | 6" POLY 6" FORK | 8" PN 5 1/4" FORK | | |
| Top | 16 15/16" | 18 3/4" | 18 5/16" | 18 3/16" | 18 1/2" | | |
| Bottom | 17 15/16" | 19 3/4" | 19 5/16" | 19 3/16" | 19 1/2" | | |

| Rear Seat Height (For Standard Frames and Standard Axle Plate Position Only) | | | | | | | |
|--|---------------------|--------------------|---------------------------|---------------------|---------------------|-----------------------|---------------------|
| REAR AXLE/HOLE POSITION | 20" PNEU POLY | 22" FP POLY | 22" PNEU LP POLY | 24" FP CLNCHR | 24" HP KEVLAR | 24" PNEU CLNCHR | 26" HP Kevlar |
| 1 AND 2 | 18 7/8" 17 3/4" | 19 1/2" 18 5/8" | 19 3/4" 18 7/8" | 20" 19 1/8" | 20 1/4" 19 1/4" | 20 3/8" 19 3/8" | 20 1/2" 20 1/8" |
| 2 AND 3 | 18 7/8" 17 3/4" | 19 1/2" 18 5/8" | 19 3/4" 17 1/2" | 18" 17 3/4" | 18 1/8" 18 1/4" | 18 1/4" 19" | 19" 19" |
| 3 AND 4 | 18 7/8" 16 5/8" | 19 1/2" 17 1/4" | 19 3/4" 17 1/2" | 18" 17 3/4" | 18 1/8" 17 1/4" | 18 1/4" 19" | 19" 19" |
| 4 AND 5 | 18 7/8" 15 1/2" | 19 1/2" 16 1/8" | 19 3/4" 16 5/8" | 18" 16 7/8" | 18 1/8" 17" | 18 1/4" 17 7/8" | 18" 17 7/8" |

| Overall Width (With Standard Camber and Padded Swing-Away Arm) | | | | | | | |
|--|---------|---------|---------|---------|---------|---------|---------|
| FRAME WIDTH | 12" | 13" | 14" | 15" | 16" | 17" | 18" |
| SPOKE WHEEL | 20 1/2" | 21 1/2" | 22 1/2" | 23 1/2" | 24 1/2" | 25 1/2" | 26 1/2" |
| W/ HANDRIMS | 20 1/2" | 21 1/2" | 22 1/2" | 23 1/2" | 24 1/2" | 25 1/2" | 26 1/2" |

| Quickie 2 | | | Quickie 2 HD | | Quickie 2 Kids | | |
|--------------------------|--|--|--------------------------|--|--------------------------|--|--|
| Weight: 27 lbs | | | Weight Capacity: 250 lbs | | Weight Capacity: 350 lbs | | |
| Weight Capacity: 250 lbs | | | | | | | |

| Quickie Recliner | | | | | | | |
|---------------------------|-----------------------|--------------------|--------------------|------------------------|------------------------|----------|--|
| Front Seat Height | | | | | | | |
| CASTER FORK MOUNTING HOLE | 5" LP POLY 6" FORK | 6" PNEU 6" FORK | 6" POLY 6" FORK | 8" PNEU 5 1/4" FORK | 8" POLY 5 1/4" FORK | | |
| TOP | 17 3/4" | 18 5/16" | 18 3/16" | 18 3/16" | N/A | N/A | |
| BOTTOM | 18" | 19 5/16" | 19 3/16" | 19 1/2" | 19 5/16" | 19 5/16" | |

| Rear Seat Height | | | | | | | |
|-------------------------|------------------------|------------------------|-------------------------|--------------------|--------------------------|--------------------|-----------------------|
| REAR AXLE/HOLE POSITION | 22" PNEU TUBULAR | 24" LATEX CLNCHR | 24" HP TEN/B-BALL | 24" HT LATEX | 26" PNEU TURBO TRD | 26" HT PNEU | 26" PNEU CLNCHR |
| 1 AND 2 | 19 3/4" 20 1/4" | 20 3/8" 19 1/8" | 20 1/2" 19 3/8" | 20 5/8" 19 1/2" | 21 1/4" 20 3/8" | 21 5/8" 20 1/2" | |
| 2 AND 3 | 18 5/8" 17 1/2" | 19 1/8" 18" | 19 3/8" 18 1/8" | 19 1/2" 18 1/4" | 20 1/8" 18 3/8" | 20 1/2" 19 3/8" | |
| 3 AND 4 | 17 1/2" 16 3/8" | 18" 16 7/8" | 18 1/8" 17" | 18 1/4" 17 1/8" | 18 3/8" 17 1/4" | 19" 17 1/8" | |
| 4 AND 5 | 17 1/2" 16 3/8" | 18" 16 7/8" | 18 1/8" 17" | 18 1/4" 17 1/8" | 18 3/8" 17 1/4" | 19" 18 1/4" | |

| Overall Width (Without Armrests) | | | | | | | |
|---|---------|---------|---------|---------|---------|---------|---------|
| Frame Width | 14" | 15" | 16" | 17" | 18" | 19" | 20" |
| SPOKE/MAG WHEEL W/ HANDRIMS & QUICK-RELEASE AXLES | 22 1/4" | 23 1/4" | 24 1/4" | 25 1/4" | 26 1/4" | 27 1/4" | 28 1/4" |
| SPOKE/MAG WHEEL W/ HANDRIMS & THREADED AXLES | 22" | 23" | 24" | 25" | 26" | 27" | 28" |

| Quickie Recliner | | | | | | | |
|------------------|---|--|--|--|--|--|--|
| Weight: | 42 lbs. (w/ swing-away footrests, height-adjustable armrests, headrest extension and mag. wheels) | | | | | | |
| Weight Capacity: | 250 lbs | | | | | | |

| Quickie 2HP | | | | | | | |
|--|--------------------------|----------------------|----------------------|---------------------------|-----------------------|---------------------|--|
| Front Seat Height (For Standard Frames Only) | | | | | | | |
| CASTER FORK MOUNTING HOLE | 3" MICROS 5 1/4" FORK | 3" MICROS 6" FORK | 3" MICROS 7" FORK | 5" LP POLY 5 1/4" FORK | 5" LP POLY 6" FORK | 5" LP PC 7" FORK | |
| TOP | 16 5/16" | 17 1/8" | 18 1/8" | 17 3/16" | 18" | 19" | |
| BOTTOM | 17 5/16" | 18 1/8" | 19 1/8" | 18 3/16" | 19" | 20" | |

| Rear Seat Height (For Standard Frames and Standard Axle Plate Position Only) | | | | | | | |
|--|------------------------|------------------------|-------------------------|--------------------|--------------------------|--------------------|-----------------------|
| REAR AXLE/HOLE POSITION | 22" PNEU TUBULAR | 24" LATEX CLNCHR | 24" HP TEN/B-BALL | 24" HT LATEX | 26" PNEU TURBO TRD | 26" HT PNEU | 26" PNEU CLNCHR |
| 1 AND 2 | 19 3/4" 20 1/4" | 20 3/8" 19 1/8" | 20 1/2" 19 3/8" | 20 5/8" 19 1/2" | 21 1/4" 20 3/8" | 21 5/8" 20 1/2" | |
| 2 AND 3 | 18 5/8" 17 1/2" | 19 1/8" 18" | 19 3/8" 18 1/8" | 19 1/2" 18 1/4" | 20 1/8" 18 3/8" | 20 1/2" 19 3/8" | |
| 3 AND 4 | 17 1/2" 16 3/8" | 18" 16 7/8" | 18 1/8" 17" | 18 1/4" 17 1/8" | 18 3/8" 17 1/4" | 19" 17 1/8" | |
| 4 AND 5 | 17 1/2" 16 3/8" | 18" 16 7/8" | 18 1/8" 17" | 18 1/4" 17 1/8" | 18 3/8" 17 1/4" | 19" 18 1/4" | |

| Overall Width (With Standard Camber and Padded Swing-Away Arm) | | | | | | | |
|--|---------|---------|---------|---------|---------|---------|---------|
| FRAME WIDTH | 12" | 13" | 14" | 15" | 16" | 17" | 18" |
| SPOKE/MAG WHEEL W/ HANDRIMS | 21 1/2" | 22 1/2" | 23 1/2" | 24 1/2" | 25 1/2" | 26 1/2" | 27 1/2" |
| W/ HANDRIMS | 21 1/2" | 22 1/2" | 23 1/2" | 24 1/2" | 25 1/2" | 26 1/2" | 27 1/2" |

| Quickie 2 HP | | | | | | | |
|------------------|---------|--|--|--|--|--|--|
| Weight: | 22 lbs | | | | | | |
| Weight Capacity: | 250 lbs | | | | | | |

| Quickie M6 | | | | | | | |
|----------------|-------|-------|-------|------|--|--|--|
| FRAME WIDTH: | 24" | 26" | 28" | 30" | | | |
| OVERALL WIDTH: | 32.5" | 34.5" | 36.5" | 38.5 | | | |
| FOLDED WIDTH: | 14" | | | | | | |

| Quickie M6 | | | | | | | |
|------------------|------------------------------|--|--|--|--|--|--|
| Weight: | 53 lbs. w/legrests (26 x 20) | | | | | | |
| Weight Capacity: | 650 lbs | | | | | | |

| Overall Width (Without Armrests) | | | | | | | |
|----------------------------------|-----|-----|-----|-----|-----|---------|--|
| FRAME WIDTH | 12" | 14" | 16" | 18" | 20" | FOLDED | |
| MAG WHEEL | | | | | | | |
| W/ HANDRIMS | 19" | 21" | 23" | 25" | 27" | 12 1/2" | |

| Quickie Recliner | | | | | | | |
|------------------|---------|--|--|--|--|--|--|
| Weight: | 28 lbs | | | | | | |
| Weight Capacity: | 250 lbs | | | | | | |

SPECIFICATIONS

Quickie Revolution

Front Seat Height (For Standard Frames Only)

| CASTER FORK | 5" MICRO | 5" POLY | 6" PNEU | 6" POLY |
|---------------|----------|---------|---------|---------|
| MOUNTING HOLE | 5 1/4" | 5 1/4" | 5 1/4" | 5 1/4" |
| TOP | N/A | 17 1/4" | 17 1/8" | 17 3/4" |
| BOTTOM | 17 1/4" | 18 1/4" | 18 7/8" | 18 3/4" |

REAR SEAT HEIGHT (FOR STANDARD FRAMES AND AXLE POSITION ONLY)

| CAMBER/REAR AXLE HOLE POSITION | 22" | 24" | 24" | 24" HT | 26" | 26" | 26" HT |
|--------------------------------|---------|---------|-----------|-----------|---------|---------|-----------|
| | PNEU | PNEU | LATEX | TEN/BBALL | HP | PNEU | TEN/BBALL |
| | | | TURBO TRD | CLINCHER | | | TURBO TRD |
| 0°, 4°/NO SPACER | 15 1/4" | 16 1/8" | 15 3/4" | 16 1/4" | 16 7/8" | 17 1/4" | 17 5/8" |
| 8°, 12°/NO SPACER | 14 1/2" | 15 3/8" | 15" | 15 1/2" | 16 1/8" | 16 1/2" | 16 7/8" |
| 8°, 4° + 3/4" | 16" | 16 7/8" | 16 1/2" | 17" | 17 5/8" | 18" | 18 3/8" |
| 8°, 12° + 3/4" | 15 1/4" | 16 1/8" | 15 3/4" | 16 1/4" | 16 7/8" | 17 1/4" | 17 5/8" |
| 0°, 4° + 1 1/2" | 16 3/4" | 17 5/8" | 17 1/4" | 17 3/4" | 18 3/8" | 18 3/4" | 19 1/8" |
| 8°, 12° + 1 1/2" | 15" | 16 7/8" | 16 1/2" | 17" | 17 5/8" | 18" | 18 3/8" |

Overall Width (With 4° of camber)

| Frame Width | 14" | 15" | 16" | 17" | 18" | 19" | 20" |
|---------------------------|-----|-----|-----|-----|-----|-----|-----|
| SpokeWheel* with Handrims | 24" | 25" | 26" | 27" | 28" | 29" | 30" |
| Quickie M6 | | | | | | | |
| Weight: 23 lbs. | | | | | | | |
| Weight Capacity: 250 lbs | | | | | | | |

Quickie 2 True Fit Program

Physical changes can cause a chair not to fit properly. To ensure proper fit, Sunrise offers one-time replacement for growth of the seat sling, back upholstery, footplates, hangers, back tubes, frame and crossbrace at no extra charge. (For up to three years from delivery on all Quickie 2 family wheelchairs shipped after November 15, 1995.)

ACTUAL MEASUREMENTS MAY VARY ACCORDING TO CHAIR CONFIGURATION AND ACCESSORIES. PLEASE CONSULT ORDER FORM FOR COMBINATIONS AND RESTRICTIONS. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

LIFETIME FRAME AND AXLE WARRANTY

We highly recommend distribution through a certified Rehab Professional when fitting and ordering any Quickie Products.

