

Jazzy **SELECT 14**

The Jazzy Select® 14 Series delivers the advantages of patented mid-wheel drive for maneuvering in tight, compact spaces. The Jazzy Select 14 is loaded with performance and convenience features like a powerful 60 amp controller, larger batteries for greater per-charge range, and an on-board battery charger.



Jazzy Select® 14
shown in Jazzy Red

800-800-8586 (US) ■ 888-570-1113 (Canada)
Visit us on the web: www.pridemobility.com

Pride®
Mobility Products Corp.

SPECIFICATIONS

Weight capacity	300 lbs.
Maximum speed	Up to 5 mph
Ground clearance	3"
Turning radius	21"
Overall length	38" without front riggings
Overall width	24.75"
Wheels	Drive: 14"
Front casters	6" solid
Rear casters	8" solid
Suspension	Limited
Drive train	Two-motor, mid-wheel drive
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	60 amp controller
Specialty controls	N/A
Battery charger	Off-board, 5 amp
Per-charge range	Up to 15 miles
Battery requirements	(2) 12 volt, deep cycle
Battery size	NF-22
Battery weight	38 lbs. each
Base weight	105 lbs.
Seat weight	37 lbs. (medium-back)
Max. seat dimensions	20" x 20"
Warranty	5-year limited warranty on frame; 1-year limited warranty on electronics; 1-year limited warranty on drive motors

COLOR CHOICES



Jazzy Red



Jazzy Blue

MODELS

Jazzy Select 14-C

Jazzy Select 14-SS

FEATURES

- Patented mid-wheel drive design for tight space maneuverability
- 14" knobby tires and optimum weight distribution provide superior traction
- NF-22 batteries for maximum range
- 5 amp, off-board charger

OPTIONS

- Depth adjustable high-back seat with headrest
- High-back seat with solid seat pan
- Cup holder
- Weather cover
- Rear basket
- Oxygen tank holder
- Cane/crutch holder
- Walker holder

RECOMMENDED LIFTS

Silver Star
Lifts & Ramps

- Backpacker® AVP
- Backpacker® Plus
- Backpacker® MV
- Full Platform
- Silver Boom 300



800-800-8586 (US) ▪ 888-570-1113 (Canada)
Visit us on the web: www.pridemobility.com

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %.

PRIDE
PERFORMANCE MOBILITY
— LIVE YOUR BEST™ —