

FAA
Approved
for air travel!



iGo Portable Oxygen System
(Model 306DS-A)

CE 0044



iGo® Portable Oxygen System

Reliable Portable Oxygen On The Go

The **iGo Portable Oxygen System** is a **lightweight, three-liter oxygen concentrator** that is capable of operating from three different power sources: AC Power, DC Power, or Rechargeable Battery.

The DeVilbiss iGo has been put through **aggressive durability testing to ensure consistent, reliable performance**. The iGo is the perfect solution to keep pace with an active lifestyle. This small, portable oxygen system provides **two modes of operation – continuous flow or PulseDose® delivery**.

The reliability and safety of **PulseDose oxygen delivery** has been proven effective in clinical testing as well as through independent tests performed by physicians and respiratory therapists.

Performance Features

- Settings 1 to 6 in PulseDose Mode or 1 to 3 lpm in Continuous Flow Mode
- Integrated PulseDose oxygen conserving technology extends the use time, offering improved comfort and increased efficiency.
- Built in OSD® (oxygen sensing device) ensures accurate oxygen delivery and reduced periodic maintenance schedule
- 3-year limited warranty for the iGo Portable Oxygen System
- 1-year limited warranty on battery
- Increased Battery Capabilities – Can last as long as 5.4 hours when operating on setting 1 in PulseDose Mode
- Audible alerts for Power Failure, Low Battery, Low Oxygen Output, High Flow/Low Flow, No Breath Detected in PulseDose Mode, High Temperature, Unit Malfunction
- Can be used with 50 foot tubing/cannula in continuous flow mode and 35 foot tubing/cannula in PulseDose mode

Parts and Accessories

DEVILBISS PART #	PRODUCT DESCRIPTION
306DS-627	Remote Humidifier Stand
444-507	Elbow Humidifier Adapter Kit
306D-413	DeVilbiss Rechargeable Battery
306CH	Battery Charger
306DS-625	Rolling Carry Case
306DS-635	Deluxe Rolling Carry Case
306DS-626	Detachable Wheeled Cart
306DS-655	Accessory Bag
306DS-611	Air Filter
306DS-652	DC Adapter
306DS-651	AC Adapter (Includes USA Power Cord)
306DS-601	USA Power Cord
306DS-602	Continental Europe Power Cord
306DS-603	UK Power Cord
306DS-604	Australia Power Cord
306DS-605	China Power Cord

NEW!



Battery Charger
(306CH)



Rolling Carry Case
(306DS-625)



Deluxe Rolling Carry Case
(306DS-635)



Accessory Bag
(306DS-655)



Detachable Wheeled Cart
(306DS-626)

Design Features

- High-performance capabilities, compact design weighing less than 20 lbs with battery
- Control Panel designed to be easily viewed whether unit is sitting on the ground or under an airplane seat
- Fast battery charge time – 2 to 4.5 hours dependent upon the flow setting
- Easy to read Battery Status Gauge indicates battery life
- Easy to access filter compartment
- Rolling carry case options feature easy access openings for cannula and external power supply

Technical Specifications

Designed to meet HCPCS Code E1392 and E1390

Weight	19 pounds (8.6 kg) with Battery; 15.5 pounds (7.0 kg) without Battery
Dimensions (H x W x D)	15" x 11" x 8" (38cm x 28cm x 20cm)
Flow Rate Settings	Settings 1 to 6 in PulseDose Mode; 1 to 3 lpm in Continuous Flow Mode
Max. Recommended Continuous Flow	3 lpm
Oxygen Concentration	91% ± 3% for all flow settings
Operating Temperature	41°F to 104°F (5°C to 40°C)
Transportation and Storage Temperature	-4°F to +140°F (-20° to 60°C)
Altitude	0 -13,123 feet (0 - 4,000 meters) tested @ ~933 hPa
Sound Level (3.0 PulseDose Mode)	40 dBA



DeVilbiss Healthcare LLC | 100 DeVilbiss Drive | Somerset, PA 15501 USA
800.338.1988 | 814.443.4881 | www.DeVilbissHealthcare.com